



AUTOTROL 363 VALVE

AUTOMATIC FILTER VALVE

COMPACT, LOW-PROFILE SOLUTION FOR A BROAD RANGE OF FILTRATION APPLICATIONS

FEATURES / BENEFITS

Time-tested Duraflow flapper provides frictionless sealing for longer service life

Fiber-reinforced polymer valve body for superior strength and durability, non-corrosive, and UV-resistant

Optical sensor for precision cycle positioning

Fully adjustable 3 cycle control for efficient and reliable water treatment system

Continuous service flow rate of 21 GPM with a backwash of 19 GPM

Backwash capability accommodates filter up to 36" in diameter

Super capacitor for keeping time of day during power outage

ELECTRICAL

PERFORMANCE

VALVE SPECIFICATION

Valve Body
Valve Color
Operating Pressure
Water Temperature
Ambient Temperature

PERFORMANCE

Drain Line Flow Control 4-20 gpm
Full Flow Body Service: 21 gpm
Backwash: 19 gpm
Fast Rinse: 5 gpm

VALVE CONNECTION

Tank Thread 2.5"
Inlet/Outlet 1" NPT or 1" BSP
Inlet/Outlet (center to center) 4"
Drain Location 0.75" below inlet/outlet

DIMENSION

Width 7.8"
Height 3.35"
Riser Tube Dia. 1.05"
Riser Height Flush +/- 0.5"



CONTACT INFORMATION

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209
P: 262.238.4400 | F: 262.238.4404 | WWW.PENTAIRAQUA.COM | CUSTOMER CARE: 800.279.9404

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

4002833 REV B MR14 © 2014 Pentair Residential Filtration, LLC All Rights Reserved.